



### LGAP45H Asphalt Pave (Hydraulic Transmission)

LGAP45H asphalt paver is used for paving road, plaza and so on, which is with compact structure and easily operated. It uses advanced double sets of hydraulic stretching screed and auto level sensing device to improve the reliability.

Engine	
Model	R4105
Type	Water cooled ,four cylinders
Rated power	55KW
Rated speed	2200rpm
Main Technical Specification	
Basic paving width	2000mm
Max. paving width	4500mm
Max. paving thickness	200mm
Min. paving thickness	10mm
Paving speed	0~12 m/min
Max. theoretic productivity	150t/h
Traveling Equipment	
Transmission	Full hydraulic
Under carriage	Track type
Type of Track	
Track length on ground	2500mm
Width	300mm
Working Equipment	
Screed plate	
Basic width	2000mm
Grade adjustment	0-3%
Extension model	Hydraulic to 4.5m
Vibrating frequency	
Frequency	50Hz
Hopper	
Capacity	7000kg
Discharge type	Hydraulic
Conveyor	
Independently driven	
Hydraulic control	
Electric System	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Batteries	2 sets
System voltage	24V
Dimensions	
Overall length	5270mm
Overall width	2300mm
Overall height	2500mm
Main Components	
Hydraulic pump	SAUER
Vibrating motor	SAUER
Control valve	Germany

**Shanghai Longji Construction Machinery Co., Ltd.**  
 Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China  
 Post Code: 201100      E-mail: [info@shlongji.com](mailto:info@shlongji.com)  
 Tel: +86-21-541-71571      Fax: +86-21-541-71572