



LGL20FM Mining Loader

- ▲ Articulated frame, small turning radius
- ▲ The bucket can be automatically leveled
- ▲ Hydro mechanical drive
- ▲ Low pressure wide base tyre
- ▲ All round and wide view cab which can be disassembled
- ▲ The 64KW LR4108G75 engine has strong power
- ▲ The air cleaner adopts 3-stage filtration, which has good effect.
- ▲ The power shift transmission has good reliability.
- ▲ The cab has falling objects protection function.
- ▲ Exhaust treatment system

Loading specification	
Rated load	2000kg
Rated bucket capacity	1.3M3
Max. breakout force	52KN
Dumping clearance	2400mm
Dumping reach	900mm
Engine Specification	
Model	LR4108G75
Type	In-line, 4ylinder, water cooling; direct injection diesel engine
Power	64Kw
Rated speed	2400rpm
Traveling specification	
Traveling speed: F1;F2;R1;R2	6km/h; 24km/h; 6km/h;24km/h
Grade-ability	25°
Turning radius	4830mm
Dimension specification	
Overall size (L x W x H)	5450mm x 1960mm x 2550mm
Wheel base	2200mm
Tread	1490mm
Tire specification	

Tyre size	16/70-20
Mass specification	
Operating weight	6000kg