



LGS0812GLQ Standard Asphalt Distributor

LGS0812GLQ asphalt distributor is an economical type, which is mainly composed of truck chassis, asphalt tank, asphalt pumping and spraying system, heating system, hydraulic circuit, pneumatic circuit and operation panel. It can spray rubber asphalt, hot asphalt, emulsified asphalt, modified asphalt, etc.

Engine	
Model	WD415.18
Type	Water-cooled, turbocharged
Rated power	137KW
Rated speed	2200rpm
Main Technical Specification	
Chassis model	ZZ1121G5311W
Spray width	200-4500mm
Spray volume	0.5-2.0kg/m ²
Asphalt tank volume	8000L
Asphalt heater	Imported diesel oil burner
Spray media	Hot(modified)asphalt, diluted asphalt, emulsified asphalt, etc
Spray precision	±2°
N.V.W	8000kg
Payloading capacity	7870kg
G.V.W	16000kg
Axle loading capacity(F/R)	8000/8000kg
Max. traveling speed	85km/h
Approach angle	24.5°
Departure angle	15°
Transmission System	
Mechanical type	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Ratio	
Forward	9.01,5.24,3.22,2.20,1.50,1.00
Reverse	8.30
Axle And Type	
Front axle	STEYR
Rear axle	STEYR
Ratio	4.87
Tyre size	9.00-20
Steering System	
Hydraulic steering	
Clutch And Brake	
Single-plate dry coil-spring clutch	
Service brake	Air brake
Parking brake	Mechanical
Dimensions	
Overall length	9250mm
Overall width	2496mm
Overall height	3450mm
Wheel base	5300mm
Tread(F/R)	1940/1800mm

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572